

»OPERADOR ELECTROMECHANICO LATERAL USO CONTINUO MARCA ELSAMEC MOD.MINI TAURUS.



**MINI TAURUS EVO 5,4 M - cod. 74030000
(EA-00006-00)**


This series is a result of long-term experience in the production of the motors Taurus, it was designed for the automation of residential and medium-industrial unbalanced rolling shutters with intensive use. This new systems definitely resolves problems related to the installation and replacement of the springs and the spring boxes, which are not more needed. It saves time and money.

We produce two versions of the motor: a single-phased and a three-phased version with the same technical characteristics. The single-phased model is equipped with ACRUX AB command board which, among other functions, performs soft starts and soft.

Technical characteristics

Model	Power W	Amperage A	Voltage V	Frequency Hz	R.P.M.	R.P.M. RAP 1:4	Displacement power factor	% Services S	IP Rating	Insulation Class	Torque Nm
MINI TAURUS EVO 5,4 M	450	1,4	230	50	31,5	7,9	0,81	40	IP54	F	54





» OPERADOR ELECTROMECHANICO LATERAL USO CONTINUO MARCA ELSAMEC MOD. MINI TAURUS.

Accessories



Bracket Mini-Taurus is an integral part of the system, accommodating the final gear inside: Pinion, Crown and Transmission chain.

cod. 76840000
(EA-00061-00)



Support for motor-side bracket
Transmission gear ratio 1:4
cod. 76810000



Axle \varnothing 25,4 per bandiera rap 1:4
cod. 76850000
(EA-00065-00)



Couple of flanges \varnothing 96 mm for tubes of \varnothing 101,6 x 2,6mm
cod. 70130000



Set for hand override (bar excluded)
cod. 76110000
(EA-00058-00)



Stop ring for axle \varnothing 30mm
Cod. 76730000
(EA-00069-00)



Parachute PRB 30
Cod. 76930004
(EA-00072-00)

Couple of flanges \varnothing 126,8 mm for tubes of \varnothing 133x2,9 mm
cod. 70140000

Kit for hand override from outside
cod. 76100000

Couple of flanges \varnothing 152,2 mm for tubes of \varnothing 159x3,2 mm
cod. 70150000

LIFTING CAPACITY CHART

Transmission gear ratio	Model	\varnothing TUBE in mm					
		1 3 3		1 5 9		1 6 8 , 3	
		Lifting capacity kg	Max weight shutter kg	Lifting capacity kg	Max weight shutter kg	Lifting capacity kg	Max weight shutter kg
1 : 4	MINI TAURUS 5,4	3 2 5	2 6 0	2 7 2	2 1 8	2 5 7	2 0 6

Couple of flanges \varnothing 160,7 mm for tubes of \varnothing 168,3x3,6mm
cod. 70160000

