



Puertas & Portones Automáticos, S.A. de C.V.

¡Nuestra pasión es la Solución!....

»CONOS PARA RESORTES 3-3/4", 6" PARA GARAGE DOOR.

SINGLE THREAD SPRING FITTINGS

• 3/8" -16 hardened cup point set screws installed with red heads (complies with DASMA 103)



1
6" Single Threaded
(FF-00289-00)
(FF-00290-00)
(FF-00291-00)
(FF-00292-00)

2
3-3/4" Single Threaded
(FF-00286-00)
(FF-00287-00)
(FF-00288-00)

Single Thread Spring Fittings	Max. Wire Size Diameter	Set Screw Installed	Mounting
6"	.4375"	3/8"-16 x 2" (2)	1" solid shaft - max. 30 ft. lbs. set screws torque
3-3/4"	.4062"	3/8"-16 x 1-1/2" (2)	1" tube or solid shaft - min. 1/2 turns on set screws

NOTE: 3-3/4" stationary spring fitting is available with either long or short ears.
Can be combined with 6" spring fittings for duplex assembly.



(229) 288-1552

portonesautomaticos@adsver.com.mx
portonesautomaticos@prodigy.net.mx



RESIDENCIAL



COMERCIAL



INDUSTRIAL

MEMBER



International Door Association



V01.20

(229) 927-5107, 167-8080, 167-8007, 151-7529.



www.adsver.com.mx