

STANLEY®



Puertas & Portones Automáticos, S.A. de C.V.

¡Nuestra pasión es la Solución!...

» PUERTA AUTOMATICA GIRATORIA SERIE 1500A

Stanley Rush Series 1500A - Automatic Revolving Door

- Automatic center shaft revolving door in 3 or 4 wing configuration
- Custom designs and sizes to meet our customers exacting needs
- Narrow stile construction and hair line joints for architectural elegance
- Concealed heavy duty collapsing mechanism and tapered roller bearings



AN ELEGANT, HIGH QUALITY AND ENERGY EFFICIENT AUTOMATIC REVOLVING DOOR
ENTRANCE WITH ENHANCED SAFETY

- PLC control with on board diagnostics for easy, rapid service
- Full perimeter weather seals for energy efficiency
- Upgraded Sensor package designed for added safety
- Optional Rushclad - adhesive applied wrap around design cladding for high quality, long lasting finish

(229) 288-1552

portonesautomaticos@adsver.com.mx
portonesautomaticos@prodigy.net.mx



RESIDENCIAL



COMERCIAL



INDUSTRIAL

MEMBER



International Door Association



V07.16

(229) 927-5107, 167-8080, 167-8007, 151-7529.



www.adsver.com.mx



» PUERTA AUTOMATICA GIRATORIA SERIE 1500A

Stanley Rush Series 1500A - Automatic Revolving Door

Series 1500A Automatic Product Specifications:

Description	Standard Configuration	Options
Diameters	Up to 12' (3700 mm)	Custom diameters available
Heights	7' (2130 mm) to 8'6" (2600 mm) door opening height	
Wings	3 or 4 wing	
Sweeps	Rubber/Felt sweeps	
Locks	Concealed Deadbolt into bottom rails	
Finishes	Clear or bronze anodized standard	Paint or cladding in Rushclad Stainless Steel or Muntz, hair line joints
Collapsing	Emergency bookfold – concealed in rails, ceiling and floor	
Canopy	12" (300 mm) minimum	Custom heights, extended, as required
Drum glass	1/4" (6 mm) tempered glass	Consult factory
Wing glass	1/4" (6 mm) tempered glass, factory glazed	
Wing Rails/Stiles	3 - 15/16" (100 mm) top and bottom rails, 1/3-4"(45 mm) stiles	
Bottom bearings	Tapered steel roller bearings	
Speed control	Automatic overhead, PLC programmable Slow speed activation – 1/2 design speed Emergency stop buttons included	
Ceiling	Two piece circular aluminum, standard	To match special finish, or cladding
Roof	Full circular to match finish	
Lights	Two LED lights per door, 3-1/4" (82 mm) diameter	
Custom Options	Consult Factory	
Design/testing	ANSI/BMHA A156.27, ASTM E-283	Speakers/Enunciator for customer awareness Floor grilles radius cut from stainless steel sheet

Door Diameter	Opening Width	Enclosure Dept
3 WING		
10 ft.	55 3/4" (1416 mm)	104 5/8" (2657 mm)
11 ft.	61 3/4" (1568 mm)	115" (2921 mm)
12 ft.	67 3/4" (1721 mm)	129 3/8" (3286 mm)
4 WING		
10 ft.	80 5/8" (2048 mm)	86" (2657 mm)
11 ft.	89 1/8" (2264 mm)	94 1/2" (2400 mm)
12 ft.	97 5/8" (2480 mm)	103" (2616 mm)

Based on outside diameters of doors

